

Technical data

General specifications

Operating frequency Transfer rate

Interface

Physical

System requirements Operating system

Ambient conditions

Ambient temperature Mechanical specifications

Connection

Dimensions

2.4 GHz (ISM band) max. 115 kBit/s

Bluetooth v1.2 Profil SSP (Serial Port Profile) Detection range up to 100 m

Microsoft Windows 2000, NT or XP MAC OS, Linux, UNIX oder andere

0 ... 70 °C (273 ... 343 K)

System connector for connecting cable USB 1.1 RS 232 PS/2 configured for RS 232 81 mm x 70 mm x 25 mm

Model Number

ODZ-MAH-B15-R2

Bluetooth modem, configured for RS 232

Features

- Wireless connection with Bluetoothcompatible handheld unit
- Safe data transfer thanks to bidirectional communication

Function

The Bluetooth Modem ODZ-MAH-B15-R2 offers you the possibility of the wireless connection of Bluetooth-compatible devices from the I*T-HH20 product family with your computer and the transfer of the read data by radiotelegraphy.

Due to the simple installation and a range of up to 100 m the Bluetooth Modem ODZ-MAH-B15-R2 is ideal for this purpose, provided your Bluetooth-compatible device is mobile and its cables are not prone to interference.

The modem is already pre-configured exworks for the cabling of the RS 232 interface of the computer.

Note: The RS 232 connection cable is not included in the delivery package.

ODZ-MAH-CAB-R2

Connection cable RS 232 interface

Subject to reasonable modifications due to technical advances.

Copyright Pepperl+Fuchs, Printed in Germany