



### Model Number

**LLR 18/30-1,6-0,75-QW 1x4**

Glass fiber optic - diffuse with metal silicone covering

### Features

- Optical face axial

### Series

#### Fiber optic amplifiers

Device series GLV30

### Description

#### Attention:

Fibre optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



### Technical data

#### General specifications

Fiber optic length	l	750 mm
Fiber optic diameter	d	6.5 mm
Adapter form		18/30
End piece		Thread / cylindrical right angle
Bending radius		min. 22 mm
Fiber bundle diameter		1.6 mm optical face: 2 mm <sup>2</sup>
Fiber configuration	Fv	statistical mixed
Approvals		CE
Angle of divergence		approx. 68 °

#### Ambient conditions

Ambient temperature		-20 ... 95 °C (-4 ... 203 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
Storage temperature		-20 ... 85 °C (-4 ... 185 °F)

#### Mechanical specifications

Protection degree		IP65
Material		
Optical face		glass
Sheathing		Metal-silicon
Core		Glass fiber
End piece		Stainless steel 1.4305 / AISI 303
Adapter		Polyamide PA 6.6
Extraction force		at probe at 20°C: 120 N

### Dimensions

